

# FUEL FILTERS - SPIN ON CARTRIDGE STYLE

FFS-10

## Product Features

- High Flow Fuel Filter, complete with 10 micron Spin-On style filter cartridge
- Aluminum Die Cast Head, vacuum impregnated for leakproof operation
- Inlet & Outlet threaded 1" (F)
- Fits spin on cartridges with 1-1/2"-16 UNF threads
- Designed for use on both mobile & stationary fuel tanks and on gasoline & diesel fuel pumps
- Ideal for use in construction & agricultural applications
- Removes particulate contaminants such as dirt, dust & rust
- Replacement Spin-On Filter cartridges available as spare

## RECOMMENDED USE

Gasoline, Diesel Fuel

## DO NOT USE

With water based products, Aviation Fuels, Race Fuels etc.



Aluminum die cast filter head threaded 1" at the inlet

Aluminum die cast filter head threaded 1" at the outlet

FFS/10/N

Spin-On Filter Cartridge



**Max. Working Pressure**  
50 PSI (3.45 BAR)

## FLOW RATE



**Max. Flow: 20 GPM (75 LPM)**

## Ordering Information

CAT. NR.	ORDERING NR.	FILTER ELEMENT	INLET/OUTLET
<b>Fuel Filter</b>			
FFS/10/BSP	45900	10 µ Filter	1" BSP (F)
FFS/10/N	45901	10 µ Filter	1" NPT(F)
FFS/10WB/BSP	45902	10 µ Water Block Filter	1" BSP (F)
FFS/10WB/N	45903	10 µ Water Block Filter	1" NPT(F)
<b>Replacement Cartridge</b>			
FF/FFS/10	45910	10 µ Filter	
FF/FFS/10-WB	45911	10 µ Water Block Filter	

FF/FFS/10



Mounting Holes  
5/16"-18 BSW



1-1/2"-16 UNF  
Threads