

Product Features

- Rotary barrel pump with Aluminum Die Cast pump body, heavy duty zinc die cast rotor & vanes
- Ideal for use in Industrial & Automotive applications
- Includes a 2" Cast Iron bung adaptor & die cast aluminum handle with security locking latch
- Complete with a 3 pc threaded suction tube for use on 15 gallons (50 litre) – 55 gallons (205 litre) barrels



WETTED COMPONENTS

Aluminum, Zinc, Steel, NBR/Viton & PVC nitrile*

*only for RB/1H

RECOMMENDED USE

Gasoline, Diesel fuel, Kerosene, Antifreeze* & Lubricating oils upto SAE 60

*Only pumps with Viton Seal

DO NOT USE

With Corrosive liquids, Solvents, Acids, Alkalis etc.



Variants



RB/1
Pump complete with steel discharge spout

1.8 m PVC nitrile delivery hose with metal nozzle, spring and hose clamp

Also available as spare:
Cat. Nr. SA/HOS/AA92/A2
Ordering Nr. 44339

! WARNING

Fuels containing Ethanol will cause more frequent replacement of rubber parts

Never operate the pump near fire or source of spark. Some media may be explosive & dangerous to pump

Ordering Information

CAT. NR.	ORDERING #	SEALS	DISCHARGE SPOUT
RB/1	44030	NBR	Steel
◆ RB/1V	44032	VITON	Steel
RB/1H	44031	NBR	1.8 m hose with nozzle, spring & hose clamp

◆ New



4 litres (1.05 gal.) / 20 rotations