



a PRO20-115AD



b PRO20-115MD



c PRO20-115PO
PRO20-115PO/XTS
PRO20-230PO

GPRO[®]

PROFESSIONAL GRADE
> Fuel Transfer Pump

20
GPM
76 L/min

230V
AC
Fixed

PRO20-230



ELECTRICAL

Input:	230V, 50 Hz
Type:	Carbon Vane
Current Draw:	2.5 amp
Motor:	1725 RPM, 1/3 HP, UL Listed to US and Canadian Standards

OPERATING PRESSURE

22 psi (1.52 bar) - High Pressure

OPERATING TEMPERATURE

-20°F to 125°F (-29°C to 52°C)

PUMP HOUSING

Powder Coated Cast Iron

PERFORMANCE

Flow Rate:	20 GPM (76 L/min)
Duty Cycle:	30 min. ON, 30 min. OFF

MECHANICAL CONNECTIONS

Inlet / Outlet: 1 in. NPT

Mounting: 2 in. NPT

WARRANTY

4 Year Pump

SEE ACCESSORIES FOR OPTIONAL EQUIPMENT > Starting on page 47

> Ordering Information

	Part No.	Model	Nozzle	Hose	Suction Pipe	Temperature Rating
115V	a 503000-03	PRO20-115AD	Automatic	18 ft.	Included	-20° F (-29° C)
	b 503000-02	PRO20-115MD	Manual	18 ft.	Included	-20° F (-29° C)
	c 503000-01	PRO20-115PO	None	None	None	-20° F (-29° C)
	c 503000-05	PRO20-115PO/ XTS	None	None	None	Tested to -40° F (-40° C)

230V	c 523000-01	PRO20-230PO	None	None	None	-20° F (-29° C)
-------------	--------------------	-------------	------	------	------	-----------------

- Powder coating creates a durable and long-lasting finish that resists corrosion, withstands chipping, scratching, fading, and wearing
- Extreme Temperature Series (XTS) model available